

TECHNICAL DATA SHEET

CBX400-50K PX35 W72

Biaxial fabric ±45° in Carbon fibre



Layer	Angle Tolerance	Fiber	Plan	Tex	Areal Weight gr/M²	Tolerance
Oº	-	Polyester yarn	M25	8	8	±5%
- 45º	±1º	Carbon: Zoltek PANEX PX35 W72 50K	M25	3790	200	±5%
+ 45º	±1º	Carbon: Zoltek PANEX PX35 W72 50K	M25	3790	200	±5%
		TOTAL gr/M²	-	-	408	±5%

Characteristics for fabric

Lunghezza rotolo - standard roll length:	LM	50	±1 LM
Larghezza rotolo - standard roll width:	MM	1270	± 20mm
Peso netto rotolo - net roll weight:	KG	25,9	± 1,30Kg
Tolleranza sulla grammatura – areal weight tolerance:	Gr/M²	±5%	± 20gr/M²
Grammatura teorica – theoretical areal weight:	Gr/M²	408	
Identificazione rotolo - ident roll:	CBX400-50K F	X35 W72	
Tipo di legatura - knitting type:	pillar		
Filo di legatura – stitch yarn:	Polyester, textu	ırated, 8.0 tex	

Characteristics for filament yarn

Tipo fibra – Type:	Zoltek PANEX PX35 W72 50K		
Size amount:	1.50 %*		
Produttore – Manufacturer:	Zoltek Corporation		
Densità volumetrica – Volumetric density:	g/cm³ 1.81		
Nr. filamenti - Number of filaments:	50000		
Carico di rottura a trazione – Tensile strength:	Mpa 4137*		
Modulo a trazione – Tensile modulus:	Gpa 242*		
Allungamento a rottura – Elongation at break:	1,5 %*		

^{*} All these informations can be used for material selection purposes only.



TECHNICAL MANAGER Ing. Giovanni Fardin

DNV-GL TYPE APPROVED PRODUCT - Cert. No. TAKOOOOONV

NB: THIS DOCUMENT IS COMPUTER GENERATED AND IT'S VALID WITHOUT SIGNATURE

Confidentiality Statement

The information, data, and charts embodied in this Technical Data Sheet (TDS) are strictly confidential and are supplied on the understanding that they will be held confidentially and not disclosed to third parties without the prior written consent of Selcom srl with registered office in 31010 Fregona (TV) ITALY-Via Della Torre no. 17 –For further info, please contact Selcom srl at info@selcom-srl.com or fax to no. +39 0438 58 51 72 / 91 60 49

SELCOM Srl is a weaver of technical textiles from continuous filaments (rovings). All information supplied by or on behalf of SELCOM Srl in relation to its products, whether in the nature of data, recommendations or otherwise, has been given in good faith and in compliance with technical and commercial information supplied by raw materials (fibre) manufacturers. All information aforementioned are supported by its own experience and

believed reliable but SELCOM SrI declines all responsibility in respect of the application, processing ore use of the aforementioned information or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify or any consequence thereof. SELCOM SrI believes that it is the user that shall determine the suitability of a product for its end-use and the user that assures all liability in connection therewith.

