

Product Data Sheet

Fabric Construction

Fibre Type: E-Glass Construction: 0/90

Fabric Weight: 572 gsm +/- 5%

Stitching Fibre

Stitching Thread: Texturised Polyester W

Stitch DTex: 78
Stitch Gauge: 6.0 gg
Stitch Length: 3.33 mm

Stitch Type: 1/2 Pillar Tricot

Stitch Weight: 6 gsm


Ply Construction

٥°

Fibre Specification: E-Glass
Fibre Tex: 1200 tex
Gauge: 6 gg
Ply Weight: 283 gsm

90°

Fibre Specification: E-Glass
Fibre Tex: 300 tex
Gauge: 24 gg
Ply Weight: 283 gsm



Customisation

Customer Code and Description: Customer Specified

Fabric Width: 1270mm (+/- 5mm) - or tapes on application

Tracer Threads / Tapered Edges: Customer Specified
Approved Fibres: On Application
Roll Weight / Length: Customer Specified
Cardboard Core: Customer Specified
Packaging: Customer Specified

For more information

Hexcel is a worldwide supplier of composite materials to aerospace and industrial markets. Our comprehensive range includes:

- HexTow® carbon fibres
- HexForce® reinforcements
- HiMax[™] non-crimp fabrics

• HexMC® moulding compounds

- · HexPly® prepregs
- HexFlow® RTM resins
- Redux® adhesives
- HexTool® tooling materials Engineered core
- HexWeb® honeycombs
- - · Engineered products

 Acousti-Cap® sound attenuating honeycomb

For quotes, orders and product information call +44 116 275 2200. For other worldwide sales office telephone numbers and a full address list, please go to:

http://www.hexcel.com/contact/salesoffice