



HiMax™ GGL6522

FGE198 [GE, 300, +45/-45]



Product Data Sheet

Fabric Construction

Fibre Type: E-Glass
 Construction: +45/-45
 Fabric Weight: 305 gsm +/- 5%

Stitching Fibre

Stitching Thread: Texturised Polyester W
 Stitch DTex: 35
 Stitch Gauge: 6.0 gg
 Stitch Length: 2.5 mm
 Stitch Type: Pillar
 Stitch Weight: 3 gsm


Ply Construction

Layer 2: +45°

Fibre Specification: E-Glass
 Fibre Tex: 136 tex
 Gauge: 20 gg
 Ply Weight: 151 gsm

Layer 1: -45°

Fibre Specification: E-Glass
 Fibre Tex: 136 tex
 Gauge: 20 gg
 Ply Weight: 151 gsm



Customisation

Customer Code and Description:	Customer Specified
Fabric Width:	1270mm (+/- 5mm) - or tapes on application
Tracer Threads / Tapered Edges:	Customer Specified
Approved Fibres:	On Application
Roll Weight / Length:	Customer Specified
Cardboard Core:	Customer Specified
Packaging:	Customer Specified



HiMax™ GGL6522

FGE198 [GE, 300, +45/-45]



Product Data Sheet

For more information

Hexcel is a worldwide supplier of composite materials to aerospace and industrial markets.

Our comprehensive range includes:

- HexTow® carbon fibres
- HexForce® reinforcements
- HiMax™ non-crimp fabrics
- HexPly® prepregs
- HexMC® moulding compounds
- HexFlow® RTM resins
- Redux® adhesives
- HexTool® tooling materials
- HexWeb® honeycombs
- Acousti-Cap® sound attenuating honeycomb
- Engineered core
- Engineered products

For quotes, orders and product information call +44 116 275 2200. For other worldwide sales office telephone numbers and a full address list, please go to:

<http://www.hexcel.com/contact/salesoffice>