

Product Data Sheet

Fabric Construction

Fibre Type: E-Glass Construction: 0/+45/-45

Fabric Weight: 818 gsm +/- 5%

Stitching Fibre

Stitching Thread: Texturised Polyester W

Stitch DTex: 78
Stitch Gauge: 6.0 gg
Stitch Length: 2.5 mm

Stitch Type: 1/2 Pillar Tricot

Stitch Weight: 7 gsm

Ply Construction

00

Fibre Specification: E-Glass
Fibre Tex: 1200 tex
Gauge: 8.47 gg
Ply Weight: 400 gsm

Layer 3: +45°


Fibre Specification: E-Glass
Fibre Tex: 300 tex
Gauge: 12 gg
Ply Weight: 200 gsm

Layer 2: 90°

Fibre Specification: E-Glass
Fibre Tex: 68 tex
Gauge: 4 gg
Ply Weight: 11 gsm

Laver 1: -45°

Fibre Specification: E-Glass
Fibre Tex: 300 tex
Gauge: 12 gg
Ply Weight: 200 gsm



Customisation

Packaging:

Customer Code and Description: Customer Specified

Fabric Width: 1270mm (+/- 5mm) - or tapes on application

Customer Specified

Tracer Threads / Tapered Edges: Customer Specified Approved Fibres: On Application Roll Weight / Length: Customer Specified Customer Specified Customer Specified



For more information

Hexcel is a worldwide supplier of composite materials to aerospace and industrial markets. Our comprehensive range includes:

- HexTow® carbon fibres
- HexForce® reinforcements

• HexMC® moulding compounds

- HiMax[™] non-crimp fabrics

- HexPly® prepregs
- HexFlow® RTM resins
- Redux® adhesives
- HexTool® tooling materials Engineered core
- HexWeb® honeycombs
- Acousti-Cap® sound attenuating honeycomb
- · Engineered products

For quotes, orders and product information call +44 116 275 2200. For other worldwide sales office telephone numbers and a full address list, please go to:

http://www.hexcel.com/contact/salesoffice