



COX[™] ElectraFlow[™] Dual Ultra High performance, flexibility and controlled speed

DISPENSING





COX[™] ElectraFlow[™] Dual Ultra High performance, flexibility and controlled speed

The COX[™] ElectraFlow[™] Dual Ultra has been engineered to provide the best 2-component battery dispensing performance available today. Designed for the professional and specialist trade user across all industry sectors who demand a reliable and high performance dispensing tool.

Delivering high material output in a precise and controlled manner.

The fully integrated application system features first-in-class cordless technology, powered by the latest 18V lithium-ion batteries and chargers utilizing the CoolPack battery technology from Bosch Professional batteries.

ElectraFlow Dual Ultra provides the greatest flexibility; the twin rack drive platform ensures even high viscosity materials maintain their mixing ratio throughout the dispensing cycle. Interchangeable cartridge holding straps and plungers allow for quick and easy configuration - maximizing productivity in demanding applications. The ergonomic design provides the user with a perfectly well balanced tool, for best dispensing performance the finger-tip control features an overload shut-off and anti-drip mechanism preventing material discharge.

The electronics and software technology combined with intelligent force management ensures that users have complete control over the output speed of the dispenser.

ElectraFlow Dual Ultra includes 2-year warranty for dispenser, battery and charger.

Applications







Bonding

Repair

Sealing

Model shown: ElectraFlow Dual Ultra VBE 400 MR Warranty: 2-year warranty for dispenser, battery and charger





Shimming

COX[™] ElectraFlow[™] Dual Ultra High performance, flexibility and controlled speed

A tool platform that provides the greatest flexibility in dispensing across a range of 2-component platforms, including high viscosity materials.

COX[™] ElectraFlow[™] Dual Ultra MIXPACTM Application

System Overview

The ElectraFlow[™] Dual Ultra offers the compatibility with the following MIXPAC[™] application systems.



Bosch Professional battery and charger

ElectraFlow[™] Dual Ultra VBE 400 MR features first-in-class cordless technology powered by the latest 18V lithium-ion batteries and chargers utilizing the CoolPack battery technology from Bosch Professional batteries.



The MIXPAC[™] F-System

Manufactured from high quality, chemical resistant plastics to meet stringent shelf-line stability and metering requirements for your formulated products. Suitable for the ElectraFlow Dual Ultra 400mL volume and mixing ratios 1:1, 2:1, 4:1, 10:1 – combined with the Helix and Quadro mixing tips.

0 + 2

A solution provider for material with flow issues - ideal for high viscosity material that is difficult to dispense. No cross contamination thanks to specific interface design, available for 400mL cartridges with mixing ratio 2:1, 10:1 combined with T-mixer mixing tips.



The Mixers

A wide range of mixers of the MIXPAC[™] and QUADRO[™] type for different applications with the 2-component Systems.



CoolPack battery technology

Bosch Professional batteries heat dissipating housings improve product safety by preventing possible overheating, prolonging battery life and extending runtime.



Interchangeable straps and plungers

Interchangeable cartridge holding straps and plungers allow for quick and easy configuration - maximizing productivity in demanding applications.



Variable speed dial

Nine speed settings and a variable speed trigger give the user the control they need for a high quality finish.



The MIXPAC[™] C-System

Manufactured from high quality, chemical resistant plastics to meet stringent shelf-line stability and metering requirements for your formulated products. Suitable for the ElectraFlow Dual Ultra 400mL volume and mixing ratios 1:1, 2:1, 4:1, 10:1 - combined with dedicated mixing tips.

The MIXPAC[™] Blueline System




Fingertip control for

optimal dispensing



twin rack platform






Variable 9-speed dial

A 2-component battery powered bead 400mL dispenser for cartridges.


Specifications	Dimensio
 Weight: 3.8kg / 8.4lbs Frame Length: 203mm / 8.0in Maximum Thrust: 5.0kN Voltage: 18V Battery Capacity: 2.0Ah, 4.0Ah Battery Charge Time: 35min (2.0Ah), 45min (4.0Ah) Battery Type: Li-ion Handle Material: PC/ABS Frame Material: Steel /Aluminum Tool Component Approvals: IBS EN 62841, CE, REACH, RoHS Cartridge Ratio: 1:1, 2:1, 4:1, 10:1 Viscosity: Medium/High Standard Color: Grey/Black Customized versions on demand 	4.5in 4.5in
MIXPAC™ C-System	MIXPAC™ F-Systen



Model shown: ElectraFlow Dual Ultra VBE 400 MR with 10:1 cartridge, plungers and straps




ons





COX™ ElectraFlow™ Dual Ultra

High performance, flexibility and controlled speed



Sulzer Mixpac AG Rütistrasse 7 CH 9469 Haag, Schweiz Tel. +41 81 772 20 00 coxsales@sulzer.com www.coxdispensers.com **Dispensing Expertise**

© Sulzer Mixpac 2018