

EN

## Product Information

### COLOURING PASTE FOR EPOXY AND POLYURETHANE RESINS

**ELANTAS EUROPE Sales offices:**

Strada Antolini n°1 loc. Lemignano  
43044 Collecchio (PR)  
Italy

Tel +39 0521 304777  
Fax +39 0521 804410

Grossmannstr. 105  
20539 Hamburg  
Germany  
Tel +49 40 78946 0  
Fax +49 40 78946 349

[info.elantas.europe@altana.com](mailto:info.elantas.europe@altana.com)  
[www.elantas.com](http://www.elantas.com)

Manufactured: Ma

**COLOURING PASTE for EPOXY and POLYURETHANE RESINS****Typical product characteristics**

PRODUCT NAME	COLOUR
COL 101	WHITE
COL 34	BLACK
COL 35	YELLOW RAL 1004
COL 36	BLUE RAL 5002
COL 37	RED RAL 3002
COL 38	GREEN RAL 6016

Above dispersions can be added to the epoxy or polyurethane resins in the amount of 0,5-2% to obtain the expected shade.

It is good practice to homogenize the material before its use and to disperse it trying to avoid a large entrapment of air.

De-aeration before use is advisable in case of highly viscous material.

In case of use with unfilled material the pigments tend to settle over the time so if the colored material is not used immediately it is advisable to re-homogenize it.

These pastes can be added also to hardener but the stability of the colour must be checked case by case.

The product can be stored over two years in the original sealed container stored in a cool and dry place.

Refer to the data sheet and comply with regulations relating to industrial health and waste disposal.

emission

date:  
revision n. 00

December

2008

The information given in this publication is based on the present state of our technical knowledge but buyers and users should make their own assessments of our products under their own application conditions.